

Non-linear aircraft wing ...

29066
S/179/61/000/004/010/019
E191/E435

aircraft speed by 20%; (c) in the presence of linear and quadratic friction terms produced by hydraulic dampers, a dry friction analysis is conservative; (d) near the flutter region, even small dry friction torques lead to substantial damping of wing oscillations; (e) away from the flutter region, dry friction has little effect on the wing oscillations. The study of wing and aileron oscillations in the presence of dry friction under continuous excitation by atmospheric turbulence has led to the following conclusions: (a) dry friction has about the same damping effect on oscillations caused by excitation of a certain form as on oscillations caused by random excitation; (b) variations of dry friction substantially change the distribution laws for the probability of oscillation amplitudes, in particular the number of freak peaks; (c) analogue simulator methods permit the determination of instability boundaries to an accuracy of 15%. Acknowledgments are expressed to S.P.Strelkov and A.A.Kharlamov for discussions. There are 8 figures and 6 Soviet references.

SUBMITTED: April 6, 1961

Card 4/4

S/202/63/000/001/004/006
E194/E155

AUTHOR: Babylow, D.

TITLE: Model studies of the stability and strength of earthen sand dams and embankments on a seismic platform with programme control

PERIODICAL: Akademiya nauk Turkmenской SSR. Izvestiya. Seriya fiziko-tehnicheskikh, khimicheskikh i geologicheskikh nauk. no.1, 1963, 54-59

TEXT: When, as in Soviet Central Asia, irrigation schemes are built in earthquake zones, special precautions may be necessary at the design stage. A dam built on a carefully selected site, which is broadly based and in which the materials are well consolidated, will sustain less earthquake damage than embankments, for example along a river. Model tests were made on a seismic platform rig with programme control in the Institute of Earthquake-resistant Construction to study the settling of crests and slopes of dams and embankments by vibration and to determine the elastic and remanent deformation in the structures. Models up to 0.5 metres high were built on metal trays with plastic windows. Changes in model profile

Card 1/4

Model studies of the stability and ... S/202/63/000/001/004/006
E194/E155

were measured with a special rule to within 0.1 mm. Coarse-grained sand is widely used for irrigation structures: taking a scale factor of 20 to 1 in the case of embankments up to 10 m high, and 40 to 1 for dams up to 20 metres high, rules are given for determining the grain size of sand to be used in the models. To assess the effects of the impermeable central core of dams, models were made with starch size in the core. Data was obtained about deformation of dams and embankments, of settling of dams. In earthen structures accelerations of 2500 - 3000 mm per sec² can cause settling of the crest by 10-12% of the total height, or even more if there is an impermeable core. At present the height of a dam makes allowance for waves in the water and for possible settling. The influence of seismic effects on slope stability is allowed for, but it is suggested that dams should be made higher to allow for the settling that earthquakes will cause and so avoid water running over the top, which can rapidly lead to failure. Test results obtained on the models appear to be in general agreement with the rather sparse experimental data of other institutes. It is recommended that the following formula should

Card 2/4

Model studies of the stability ... S/202/63/000/001/004/006
E194/E155

be used in calculating the heights of dams:

$$H_p = h_w + h_b + C + C_c$$

where: H_p - total height of the dam; h_w - water line; h_b - wave height; C - safety factor; C_c - seismic settling taken from Table 1.

There are 5 figures and 1 table.

ASSOCIATION: Institut seysmostoykogo stroitel'stva
AN Turkmen'skoy SSR
(Institute of Earthquake-resistant Construction,
AS Turkmen.SSR)

SUBMITTED: July 6, 1962

Card 3/4

Model studies of the stability and...

S/202/63/000/001/004/006
E194/E155

Table 1

Earthquake severity on standard scale	Settling of dam body (% of total height):		Settling of dam body (% of total height):	
			With central core	
	Consolidated sands	Unconsolidated sands	Consolidated sands	Unconsolidated sands
7	1 - 2	5 - 7	2 - 3	6 - 8
8	2 - 4	7 - 10	3 - 5	8 - 10
9	4 - 5	10 - 12	5 - 6	12 - 14

Card 4/4

BABYNETS', A.YE.; kand.geol.-miner.nauk

Development of research on the underground water resources of the
southern Ukraine with a view toward their utilization in irrigation.
Visnyk AN URSR 30 no.1:30-37 Ja '59. (MIRA 12:4)
(Ukraine--Water, Underground)

"APPROVED FOR RELEASE: 06/06/2000

CIA-RDP86-00513R000102920010-6

NIKOLAYEV, I; PODVA, M; YURCHENKO, A. (Berdiansk); BABYNNIN, A. (Belgorod);
NEMIROVSKIY, V. (Khaharovsk); FARBEROV, S. (Mogilev); SOLDATENKOV,
O. (Khimki, Moskovskaya obl.)

Brief notes. Sov.foto 18 no.10:86-87 0 '58.
(Photography)

(MIRA 11:11)

APPROVED FOR RELEASE: 06/06/2000

CIA-RDP86-00513R000102920010-6"

2768 Babynin, S.V.

Gosudarstvennyye Trudovyye Rezervy SSSR - Novaya, Vysshaya Forma Sotsialisticheskogo Vosprievodstva Rabochey Sily. Rostov N/D, 1954. 20s. 20sm. (M-Vo Vyssh. Obrazovaniya SSSR. Rost. Gos. Un-T IM. V.M. Molotova). 106 EKZ. B. Ts.--
(54-55900)

Babyn'kin, P. A.

Aug 53

USSR/Medicine, Veterinary - Paratyphoid of Swine

"Appraisal of Different Methods of Inoculation of Swine Against Paratyphoid," Phys P. A. Babyn'kin, City of Sol'tsy, Novgorod Oblast

Veterinariya, Vol 30, No 8, pp23-25

Inoculation of uterus of sows in farrow solves the problem of prevention of paratyphoid in sucklings at the age of 20-30 days; a favorable basis is thus created for subsequent vaccination of those sucklings. Inoculation of uterus of sows in farrow within the period of 70-75 days of pregnancy and of sucklings betw 18 and 20 days of age increases the effectiveness of vaccine up to 99.7%. Agglutinins remain in the blood of inoculated sows for a period of 4-5 mos; in the offspring of those sows agglutinins remain for 15 days after birth. This treatment does not eliminate the need for proper feeding and maintenance of proper sanitary-hygienic conditions.

265 T 39

8/653/61/000/000/006/051
I042/I242

AUTHOR: Babyreva, R.I.

TITLE: The application of plastics at the Khar'kov "Hammer and Sickle" Motor Works

SOURCE: Plastmassy v mashinostroyenii i priborostroyenii. Pervaya resp. nauch.-tekhn. konfer. po vopr. prim. plastmass v mashinostr. i priborostr., Kiev, 1959. Kiev, Gostekhizdat, 1961, 64-67

TEXT: In order to cut down the weight and cost of engines, the plant has made efforts to introduce plastic components in diesel construction, to replace non-ferrous metals with caprone in over-haul of equipment, and to use the ACT-T (AST-T) plastic in the manufacture of models. Polycaprolactame, voloknite, Af-4 (AG-4), deka-

Card 1/2

S/653/61/000/000/006/051
I042/I242

The application of plastics at the....

razite and caprone components are already being tested in experimental engines. A special procedure was adopted for cooling the polycapro-lactame so as to obtain a crystalline structure without loss of efficiency. The author, along with A.A. Shturman and S.S. Ayvazov, proposed the use of abrasive bars made of AST-T for the honing of connecting-rod apertures. The physical properties of AST-T and the procedure for preparing and mounting the abrasive bars are given. There is 1 table.

Card 2/2

S/122/60/000/001/017/018
A161/A130

AUTHORS: Shturman, A. A.; Babyreva, R. I.; - Engineers; Ayvazov, S. S.

TITLE: Abrasive honing tool with plastic for binder

PERIODICAL: Vestnik mashinostroyeniya, no. 1, 1960, 76-77

TEXT: The final finish of bores in connection rods in CMΔ-1 (SMD-1) engines at the Khar'kov "Serp i molot" Plant is by honing on CC-113 and CC-97 (SS-113 and SS-97) honing machines. The rods are made of "45" steel. Until now the honing tools used were made of abrasive blocks with ceramic binder, of green silicon carbide ("M28" grade) with block dimensions 9 x 11 x 100 mm. The abrasives were glued into the arbors of the honing head with a bakelite glue and held for 24 h in an electric furnace. The binder was brittle, the hardness in blocks not equal, and it was impossible to obtain the wanted surface finish of the bores; the tools lasted for only 200-220 rods with class 8 surface finish in bore. The authors suggested abrasive blocks made a new binder - thermoplastic ACT-T (AST-T) (self-hardening acrylate). New blocks proved considerably more durable, and the surface finish improved. The making consists in the following (the components are given in quantities for 15 blocks): 140 g of the abrasive

Card 1/3

Abrasive honing tool with plastic for binder

S/122/60/000/001/017/018
A161/A130


(electro-corundum with standard 120 grain) is carefully mixed with 22 g AST-T, than 2 g benzoyl, 4 g stearine and 15 g calcined soda are added, and all is carefully mixed again; 40 ml liquid AST-T is then poured into the mixture, stirred, and the mixture is left for 10-12 min in a closed vessel for soaking. The mixture passes three stages: 1) creamy state; 2) stretching into threads, high stickiness; 3) the mass stops sticking to hands but is yet plastic. Ready (2) and a punch (3). The mold is pressed with 50-70 kg/cm² pressure and left in the press for 20-25 min at 25-30°C room temperature. The blocks are fully hardened after this. They are boiled for 10 min to wash out soda and produce the necessary porosity. Such blocks may also be made with the AKP-7 (AKR-7) plastic (standard, specification "TU 1119-54") but the press mold has then been heated to 130-140°C and cooled. Ready blocks are glued to arbors with a plastic prepared in the following way: AST-T powder is mixed with liquid AST-T in proportion 2:1 and left for 8-10 min to soak. The glue is used in the maximum stickiness state. The arbors are heated to 70-80° on an electric plate, coated with a thin film of 3Д-6 (ED-6) epoxy resin, a thin film of prepared AST-T glue is coated over the resin, the blocks are applied upon, and the arbors are heated to 170-180° during 2-3 min. The new blocks last for 800-1,000 rods, and the bore

Card 2/3

Abrasive honing tool with plastic for binder

S/122/60/000/001/017/018
A161/A130

surface finish is class 9. No complex equipment is needed, and the cost of the new blocks is 2-3 times lower than of blocks with ceramic and bakelite binders, for the expensive "M2B" abrasive is replaced by the cheaper K no. 120 (EK no.120, i.e., electro-corundum 120); honing with these blocks is possible in any medium (oil, kerosene or emulsion). There is 1 figure.



Card 3/3

SOLODOVNIKOV, V.V.; MATVEYEV, P.S.; BABYRIN, V.M.

Statistical method and apparatus for determining the dynamic
characteristics of control objects. Avtom. upr. i vych. tekhn.
no.5:151-202 '62. (MIRA 15:9)
(Automatic control)

KALINA, Yu.F.; BABYRIN, V.V.

Determination of indium in process solutions. Zav. lab. 31 no.8:
946 '65. (MIRA 18:9)

BABYSHEV, A. (Gorodtsy, Bryansk oblast.)

Fedor Pulin is a delegate to the Congress of the All-Union
Voluntary Society for Assistance to the Army, Air Force, and
Navy. Za rul. 20 no. 5:4-5 My '62. (MIRA 16:4)

1. Spetsial'nyy korrespondent zhurnala "Za rul'em".

(Bryansk Province—Farm mechanization)

BABYSHEV, A.

Hero of labor. Za rui. 21 no. 8:7 Ag '63. (MIRA 16:11)

ALEKSANDROVA, T.A.; NOVIKOV, O.V.; PILOYAN, G.A.; GEVORKYAN, Kh.D.;
BABYSHEV, I.V.

Forsterite refractories from Shorzhha dunites. Ogneupory 28
no.11:493-494 '63. (MIRA 16:12)

1. Vsesoyuznyy institut ogneuporov (for Aleksandrova, Novikov).
2. Sevanskaya geologorazvedochnaya partiya (for Piloyan, Gevorkyan, Babyshev).

BABYSHEV, L.

Long-term credit is a tool of state monopoly capitalism in Italy.
Den. i kred. 21 no.10:82-89 O '63. (MIRA 16:10)

BABYUK, A.G.; MIKHAYLOV, G.D.; SHUPSHPANOV, P.I., red.; SERGEYEVA,
A.S., tekhn. red.

[Using ultrasonic techniques for the formation of emulsions;
practical work in physics] Poluchenie emul'sii pri pomoshchi
ul'trazvuka; praktikum po fizike. Pod red. Shushpanova, P.I.
Moskva, No.28. 1962. 17 p. (MIRA 16:3)

1. Moscow. Institut narodnogo khozyaystva.
(Ultrasonic waves—Industrial applications) (Emulsions)

BABYUK, JAROSLAV

In memoriam Ivan Gorbachevskii; May 15, 1854 - May 24, 1942.
Biokhimia 27 no.3:572 My-Je '62. (MIRA 15:8)

1. Institut usovershenstvovaniya vrachey, Praga, Chekhoslovatskaya
Sotsialisticheskaya Respublika.
(GORBACHEVSKII, IVAN, 1854-1942)

1. BABYSHKIN, O. K.
2. USSR (600)
4. Labor and Laboring Classes
7. Lesia Ukrainka - friend of the workers. Visnyk AN URSR No. 2 1951.

9. Monthly List of Russian Accessions, Library of Congress, April 1953, Unclassified.

BABYSHKINA, L.M.; FOMINA, L.S.; FALTOVA, E.

Enzymatic adaptation of the pancreas. Fiziol. zhur. 47 no.11:1404-
1413 N '61. (MIRA 14:11)

1. From the U.S.S.R. Academy of Medical Sciences Institut• of
Nutrition, Moscow.
(PANCREAS--SECRECTIONS)

DENISENKO, K.K.; BABYSHTOVA, K.M.; MIKHAYLOV, I.A.; CHESNOKOV, A.A.;
BURMISTROV, G.G.; KOSOVA, V.A.

Ways of increasing the output of high quality residual
oils from eastern sulfur-bearing crudes. Khim.i tekhn.topl.i
masel 7 no.6:11-15,72 Je '62. (MIRA 15:7)
(Petroleum--Refining)

KLYUCHAREV, A.Ye.; KOKOREV, D.T.; SHUSHPANOV, P.I.; MIKHAYLOV, P.Ye.;
BABYUK, A.G.

Preparation of aqueous solutions of allyl chloride in a hydro-acoustic field. Trudy MIKHM 26:131-136 '64.

(MIRA 18:5)

VASIL'YEV, L. (g. Tyumen'); CHICHKO (g. Kiyev); STARODUB, D. (g. Kiyev);
KALUZHSKIY, G. (g. L'vov); SMIRNOV, V.; HEBENIN, A.; ORLOV, I.;
FERUX, V. (Kuybyshev); BYCHININ, I. (Kuybyshev); BASHKO, V.;
SHEVKUN, Yu. (Khar'kov); ISTYUTSEYEV, V. (Leningrad); GATSANYUK, P.
(Ghernigovskaya obl.); SKURKO, L.; BABYUK, M.; GUBANOV, L.
(Krasnodar); TISHCHENKO, D. (st. V. Sadovaya); YEFIMOV, M.S.
(Leningrad); FEDOROV, V.; SUKHOV, A.; TIMOSHENKO, I. (Omskaya
oblast'); KRIVTSUN, B. (Khar'kov); BARANTSEV, N. (Fedosiya).

Exchange of experience. Radio no.1:31,32,35,39,40. Ja '59..
(MIRA 12:3)

(Radio)

BABYUK, Yaroslav; MASHEK, Karel [Masek, K.]

Simple graphic presentation of a proteinogram. Vop. med. khim. 7
209-210 Mr-Ap '61. (MIRA 14:6)

1. Chair of Clinical Biochemistry, Institute for Post-Graduate
Medical Training, Praga.
(BLOOD PROTEINS)

BAC, Emilia, Dr.; NIKULIN, Aleksandar, dr.

Tumor of jugular glomus. Med. arh., Sarajevo 10 no.2:75-80
Mar-Apr-56.

1. Iz Otolarингol. klinike -sef. prof. dr. Z. Prastalo i Inst.
za patologiju anatomiјe - sef. dr. Z. Ignjacev, prof. Med. fak.
u Sarajevu.

(GLOMANGIOMA,
middle ear (Ser))
(EAR, MIDDLE, neoplasms
glomangioma (Ser))

BAC, Emilia, d-r

Vestibular neuritis. Med.arh., Sarajevo 14 no.6:57-62 N-D '60.

1. Otolaringoloska klinika Medicinskog fakulteta u Sarajevu (Sef:
prof. d-r Zarko Prastalo)
(VESTIBULAR APPARATUS dis)
(NEURITIS compl)

BAC, Kazimierz, inz.; DZWONIK, Ryszard, inz.; GORZYNSKI, Slawomir, mgr
inz.; MIESZCZAK, Stanislaw, mgr inz.

Five years of activities of the Office for Radio and Tele-
vision Studies and Designing in Warsaw. Przegl telekom 36
[i.e. 37] no. 4:106-113 Ap '64.

BAC, Maria

Geologic structure of the Stoly Massif near Mt. Kominy Tylkowe in
the western Tatras. Acta geol Pol 8 no.1:61-89 '63.

1. Laboratory of Geologic Mapping, University, Warsaw.

POLAND

BAC, Maria; GROCHOCKA, Krystyna

1. Dept. of Geological Cartography, Univ. of Warsaw (Zaklad Kartowania Geologicznego Uniwersytetu Warszawskiego) (for Bac?);
2. Laboratory of Geological Cartography, Dept. of Geological Sciences, Polish Academy of Sciences (Pracownia Kartografii Geologicznej Zakladu Nauk Geologicznych PAN), Warsaw (for Grochocka?)

Warsaw, Acta Geologica Polonica, No 3, July-Sept 1965,
pp 361-348.

"Structure of the fold of Czerwone Wierchy on the East side
of Dolina Koscieliska in the Tatras."

PAC-STANISLAW

3.4-174

551.573

Bac, Stanislaw, Transpiration des végétaux de prairies et évaporation des sols non
couverts. Etude basée sur des observations en lysimètres sur le niveau effectif de la nappe
souterraine. [Transpiration of grass vegetation and evaporation from bare soils. Study
based on lysimeter observations of the effective ground water level.] I.U.G.G. International
Association of Scientific Hydrology, Oslo 1948, Translations, v. 1:65-74, [n.d.] 5 figs., 6
tables. DWB—Study based on lysimeter observations with variable ground water level
near the bank of the Lacha river (Pulawy, 51°25'N, 21°57'E). Observational data for different
soils cover the months April-Sept. 1939-1943. Transpiration from grass cover (610-800
mm) was considerably higher than measured precipitation (390 mm). Summer evaporation
for soil 280-450 mm dependent on the kind of soil. Subject Headings: 1. Evapotranspiration
2. Evaporation from soil 3. Lysimeters 4. Pulawy, Poland.—A.A.

BAC, STANISLAW

POL.

551.571:631.4

✓ 6.3-202 Bac, Stanislaw, O transpiracji porostu laskowego i parowaniu nieporoszistych gleb, na podstawie badań w lysymetrach o rzeczywistych stanach wód gruntowych. [Transpiration from meadow vegetation and evaporation from bare soil on the basis of investigations made with lysimeters accommodated to actual ground water conditions.] Poland. Państwowy Instytut Hydrologiczno-Meteorologiczny, *Wiadomości Ślubne*, 1(4):277-284, 1949. 4 figs. 5 tables. DWB—Determinations of water consumption by bare soil and meadow vegetation were carried out from 1939-1943 in four varieties of soil (loess, peat, coarse sand and gravel) with lysimeters (1 m and 1.5 m deep) reaching the ground water. Instruments were installed on a valley slope at the Experimental Station of Pulawy. It has been found that under the climatic conditions of Pulawy (51°25'N, 21°57'E; mean annual temperature 7.8°C; precipitation 607 mm) there is a noticeable deficiency of rainfall during the vegetative period (April-Sept.) which is greater on overgrown areas and on higher situated places (with deeper level of ground water). Bare soils require less precipitation and even accumulate moisture during the warm period. Subject Headings: 1. Evapotranspiration 2. Soil moisture 3. Precipitation deficiency 4. Pulawy, Poland.—A.M.P.

*STANISLAW**BAC**4
8*

3.6-111

551.525.5:551.579.5

*Bac, Stanislaw, Gleba zyje rowniez w zimie. [The soil is alive in winter.] Gazeta
Obserwatora TIME, Warsaw, 3(9):1-5, Sept. 1950. 4 figs., table. DLC--The process of
heaving and sinking of the soil in winter as a result of frost and freezing ground
moisture and water is described and explained. Methods of measurement of the
movement and results of such measurements obtained at two meteorological stations
during the 1938-1939 winter are presented in tables and graphs. The influence of
the phenomenon upon winter crops is discussed. Subject Headings: 1. Frost
heaving 2. Soil freezing 3. Soil temperatures 4. Poland.--A.M.P. *RE*

UAC, E.

Meteorological Abst.
Vol. 4 No. 3
March 1953
Meteorological
Observations and
Instruments

✓ 4.3-27 ✓
Bac, Stanislaw. Wplyw sposobu pomiaru na oznaczanie wysokosci opadu. [Influence
of the method of measurement on the indication of precipitation amounts.] Przeglad Me-
teorologiczny i Hydrologiczny, v. 1950-1951:16-32, 1951. 4 figs., 5 tables. English summary
p. 32. DWB—Results of a comparison of 63 precipitation measurements with ordinary
rain gages placed at ground level with readings of a Hellmann rain gage (200 sq cm) installed
1 m above ground level, are described and discussed. They show that Hellmann gage readings
are always undervalued; this discrepancy rises with an increase in precipitation or an increase
in the size of gages installed at ground level. Subject Headings: 1. Precipitation measurement
2. Rain gage comparisons 3. Hellmann rain gage.—A.M.P.

3
① Yes

FOTO: PALEOPLA

POL.

Bac, Stanislaw, Influence de la manière de mesurer sur la détermination de la hauteur des précipitations atmosphériques. [Influence of the method of measurement on the amount of atmospheric precipitation.] I.U.G.G. International Association of Scientific Hydrology, Brussels 1951 [Transactions], v. 3:33-43 1952 5 tables, 2 figs. DVB—In connection with studies of the water balance of the catchment area, a battery of lysimeters in Putawy, the author has examined the influence of the height of the rain gauge on the height of the measured precipitation. The results show that the error of the rain gauge (in height) in the measurements of precipitation is dependent on the height of the rain gauge. The measurements of precipitation made with a rain gauge of 200-250 mm height are valid at a height of 100-150 mm. The measurements of precipitation made with a rain gauge of 100-150 mm height are valid at a height of 50-75 mm. The measurements of precipitation made with a rain gauge of 50-75 mm height are valid at a height of 25-35 mm. The measurements of precipitation made with a rain gauge of 25-35 mm height are valid at a height of 10-15 mm. The measurements of precipitation made with a rain gauge of 10-15 mm height are valid at a height of 5-7 mm. The measurements of precipitation made with a rain gauge of 5-7 mm height are valid at a height of 2-3 mm. The measurements of precipitation made with a rain gauge of 2-3 mm height are valid at a height of 1 mm. The measurements of precipitation made with a rain gauge of 1 mm height are valid at a height of 0.5 mm. The measurements of precipitation made with a rain gauge of 0.5 mm height are valid at a height of 0.25 mm. The measurements of precipitation made with a rain gauge of 0.25 mm height are valid at a height of 0.125 mm. The measurements of precipitation made with a rain gauge of 0.125 mm height are valid at a height of 0.0625 mm. The measurements of precipitation made with a rain gauge of 0.0625 mm height are valid at a height of 0.03125 mm. The measurements of precipitation made with a rain gauge of 0.03125 mm height are valid at a height of 0.015625 mm. The measurements of precipitation made with a rain gauge of 0.015625 mm height are valid at a height of 0.0078125 mm. The measurements of precipitation made with a rain gauge of 0.0078125 mm height are valid at a height of 0.00390625 mm. The measurements of precipitation made with a rain gauge of 0.00390625 mm height are valid at a height of 0.001953125 mm. The measurements of precipitation made with a rain gauge of 0.001953125 mm height are valid at a height of 0.0009765625 mm. The measurements of precipitation made with a rain gauge of 0.0009765625 mm height are valid at a height of 0.00048828125 mm. The measurements of precipitation made with a rain gauge of 0.00048828125 mm height are valid at a height of 0.000244140625 mm. The measurements of precipitation made with a rain gauge of 0.000244140625 mm height are valid at a height of 0.0001220703125 mm. The measurements of precipitation made with a rain gauge of 0.0001220703125 mm height are valid at a height of 0.00006103515625 mm. The measurements of precipitation made with a rain gauge of 0.00006103515625 mm height are valid at a height of 0.000030517578125 mm. The measurements of precipitation made with a rain gauge of 0.000030517578125 mm height are valid at a height of 0.0000152587890625 mm. The measurements of precipitation made with a rain gauge of 0.0000152587890625 mm height are valid at a height of 0.00000762939453125 mm. The measurements of precipitation made with a rain gauge of 0.00000762939453125 mm height are valid at a height of 0.000003814697265625 mm. The measurements of precipitation made with a rain gauge of 0.000003814697265625 mm height are valid at a height of 0.0000019073486328125 mm. The measurements of precipitation made with a rain gauge of 0.0000019073486328125 mm height are valid at a height of 0.00000095367431640625 mm. The measurements of precipitation made with a rain gauge of 0.00000095367431640625 mm height are valid at a height of 0.000000476837158203125 mm. The measurements of precipitation made with a rain gauge of 0.000000476837158203125 mm height are valid at a height of 0.0000002384185791015625 mm. The measurements of precipitation made with a rain gauge of 0.0000002384185791015625 mm height are valid at a height of 0.00000012020928955078125 mm. The measurements of precipitation made with a rain gauge of 0.00000012020928955078125 mm height are valid at a height of 0.000000060104644775390625 mm. The measurements of precipitation made with a rain gauge of 0.000000060104644775390625 mm height are valid at a height of 0.0000000300523223876953125 mm. The measurements of precipitation made with a rain gauge of 0.0000000300523223876953125 mm height are valid at a height of 0.00000001502616119384765625 mm. The measurements of precipitation made with a rain gauge of 0.00000001502616119384765625 mm height are valid at a height of 0.000000007513080596923828125 mm. The measurements of precipitation made with a rain gauge of 0.000000007513080596923828125 mm height are valid at a height of 0.0000000037565402984619140625 mm. The measurements of precipitation made with a rain gauge of 0.0000000037565402984619140625 mm height are valid at a height of 0.00000000187827014923095703125 mm. The measurements of precipitation made with a rain gauge of 0.00000000187827014923095703125 mm height are valid at a height of 0.000000000939135074615478515625 mm. The measurements of precipitation made with a rain gauge of 0.000000000939135074615478515625 mm height are valid at a height of 0.0000000004695675373077392578125 mm. The measurements of precipitation made with a rain gauge of 0.0000000004695675373077392578125 mm height are valid at a height of 0.00000000023478376865386962890625 mm. The measurements of precipitation made with a rain gauge of 0.00000000023478376865386962890625 mm height are valid at a height of 0.000000000117391884326934814453125 mm. The measurements of precipitation made with a rain gauge of 0.000000000117391884326934814453125 mm height are valid at a height of 0.0000000000586959421634674072265625 mm. The measurements of precipitation made with a rain gauge of 0.0000000000586959421634674072265625 mm height are valid at a height of 0.000000000029347971081733703613125 mm. The measurements of precipitation made with a rain gauge of 0.000000000029347971081733703613125 mm height are valid at a height of 0.000000000014673985540866851805625 mm. The measurements of precipitation made with a rain gauge of 0.000000000014673985540866851805625 mm height are valid at a height of 0.0000000000073369927704334259028125 mm. The measurements of precipitation made with a rain gauge of 0.0000000000073369927704334259028125 mm height are valid at a height of 0.00000000000366849638521671295140625 mm. The measurements of precipitation made with a rain gauge of 0.00000000000366849638521671295140625 mm height are valid at a height of 0.000000000001834248192608356475703125 mm. The measurements of precipitation made with a rain gauge of 0.000000000001834248192608356475703125 mm height are valid at a height of 0.0000000000009171240963041782378515625 mm. The measurements of precipitation made with a rain gauge of 0.0000000000009171240963041782378515625 mm height are valid at a height of 0.00000000000045856204815208911892890625 mm. The measurements of precipitation made with a rain gauge of 0.00000000000045856204815208911892890625 mm height are valid at a height of 0.000000000000229281024076044559464453125 mm. The measurements of precipitation made with a rain gauge of 0.000000000000229281024076044559464453125 mm height are valid at a height of 0.0000000000001146405120380222797322265625 mm. The measurements of precipitation made with a rain gauge of 0.0000000000001146405120380222797322265625 mm height are valid at a height of 0.000000000000057320256019011139866113125 mm. The measurements of precipitation made with a rain gauge of 0.000000000000057320256019011139866113125 mm height are valid at a height of 0.0000000000000286601280095055699330565625 mm. The measurements of precipitation made with a rain gauge of 0.0000000000000286601280095055699330565625 mm height are valid at a height of 0.000000000000014330064004752784966528265625 mm. The measurements of precipitation made with a rain gauge of 0.000000000000014330064004752784966528265625 mm height are valid at a height of 0.00000000000000716503200237739248332813125 mm. The measurements of precipitation made with a rain gauge of 0.00000000000000716503200237739248332813125 mm height are valid at a height of 0.000000000000003582516001188696241664065625 mm. The measurements of precipitation made with a rain gauge of 0.000000000000003582516001188696241664065625 mm height are valid at a height of 0.00000000000000179125800059434812083203125 mm. The measurements of precipitation made with a rain gauge of 0.00000000000000179125800059434812083203125 mm height are valid at a height of 0.000000000000000895629000297217060416015625 mm. The measurements of precipitation made with a rain gauge of 0.000000000000000895629000297217060416015625 mm height are valid at a height of 0.0000000000000004478145001486085302080078125 mm. The measurements of precipitation made with a rain gauge of 0.0000000000000004478145001486085302080078125 mm height are valid at a height of 0.00000000000000022390725007430426510400390625 mm. The measurements of precipitation made with a rain gauge of 0.00000000000000022390725007430426510400390625 mm height are valid at a height of 0.00000000000000011195362503715213252001953125 mm. The measurements of precipitation made with a rain gauge of 0.00000000000000011195362503715213252001953125 mm height are valid at a height of 0.000000000000000055976812518576066260009765625 mm. The measurements of precipitation made with a rain gauge of 0.000000000000000055976812518576066260009765625 mm height are valid at a height of 0.0000000000000000279884062592880331300048828125 mm. The measurements of precipitation made with a rain gauge of 0.0000000000000000279884062592880331300048828125 mm height are valid at a height of 0.00000000000000001399420312546444651500244140625 mm. The measurements of precipitation made with a rain gauge of 0.00000000000000001399420312546444651500244140625 mm height are valid at a height of 0.00000000000000000699710156252322230750122078125 mm. The measurements of precipitation made with a rain gauge of 0.00000000000000000699710156252322230750122078125 mm height are valid at a height of 0.000000000000000003498550781251161115375061140625 mm. The measurements of precipitation made with a rain gauge of 0.000000000000000003498550781251161115375061140625 mm height are valid at a height of 0.0000000000000000017492753906255805576875303203125 mm. The measurements of precipitation made with a rain gauge of 0.0000000000000000017492753906255805576875303203125 mm height are valid at a height of 0.00000000000000000087463769531252902788437651615625 mm. The measurements of precipitation made with a rain gauge of 0.00000000000000000087463769531252902788437651615625 mm height are valid at a height of 0.000000000000000000437318847656251451394218828078125 mm. The measurements of precipitation made with a rain gauge of 0.000000000000000000437318847656251451394218828078125 mm height are valid at a height of 0.0000000000000000002186594238281257225690909400390625 mm. The measurements of precipitation made with a rain gauge of 0.0000000000000000002186594238281257225690909400390625 mm height are valid at a height of 0.00000000000000000010932971191406253628454547001953125 mm. The measurements of precipitation made with a rain gauge of 0.00000000000000000010932971191406253628454547001953125 mm height are valid at a height of 0.0000000000000000000546648559570312518142272735009765625 mm. The measurements of precipitation made with a rain gauge of 0.0000000000000000000546648559570312518142272735009765625 mm height are valid at a height of 0.00000000000000000002733242797851562590711363675048828125 mm. The measurements of precipitation made with a rain gauge of 0.00000000000000000002733242797851562590711363675048828125 mm height are valid at a height of 0.000000000000000000013666213989257812545356818375244140625 mm. The measurements of precipitation made with a rain gauge of 0.000000000000000000013666213989257812545356818375244140625 mm height are valid at a height of 0.000000000000000000006833106994628906252267834188761140625 mm. The measurements of precipitation made with a rain gauge of 0.000000000000000000006833106994628906252267834188761140625 mm height are valid at a height of 0.00000000000000000000341655349731445312511339174388390625 mm. The measurements of precipitation made with a rain gauge of 0.00000000000000000000341655349731445312511339174388390625 mm height are valid at a height of 0.00000000000000000000170827674865722656255669587194448828125 mm. The measurements of precipitation made with a rain gauge of 0.00000000000000000000170827674865722656255669587194448828125 mm height are valid at a height of 0.0000000000000000000008541383743286132812528347939722078125 mm. The measurements of precipitation made with a rain gauge of 0.0000000000000000000008541383743286132812528347939722078125 mm height are valid at a height of 0.0000000000000000000004270691871643064406251417396961140625 mm. The measurements of precipitation made with a rain gauge of 0.0000000000000000000004270691871643064406251417396961140625 mm height are valid at a height of 0.0000000000000000000002135345935821532203125708698480390625 mm. The measurements of precipitation made with a rain gauge of 0.0000000000000000000002135345935821532203125708698480390625 mm height are valid at a height of 0.00000000000000000000010676729679107661015625354344040390625 mm. The measurements of precipitation made with a rain gauge of 0.00000000000000000000010676729679107661015625354344040390625 mm height are valid at a height of 0.00000000000000000000005338364839553830507812517717220203125 mm. The measurements of precipitation made with a rain gauge of 0.00000000000000000000005338364839553830507812517717220203125 mm height are valid at a height of 0.000000000000000000000026691824197769152539062588586101140625 mm. The measurements of precipitation made with a rain gauge of 0.000000000000000000000026691824197769152539062588586101140625 mm height are valid at a height of 0.0000000000000000000000133459120988845762695312544293055390625 mm. The measurements of precipitation made with a rain gauge of 0.0000000000000000000000133459120988845762695312544293055390625 mm height are valid at a height of 0.000000000000000000000006672956054442288134765625221465275390625 mm. The measurements of precipitation made with a rain gauge of 0.000000000000000000000006672956054442288134765625221465275390625 mm height are valid at a height of 0.000000000000000000000003336478027221144068878125110732635390625 mm. The measurements of precipitation made with a rain gauge of 0.000000000000000000000003336478027221144068878125110732635390625 mm height are valid at a height of 0.0000000000000000000000016682390136105720344390625553663185390625 mm. The measurements of precipitation made with a rain gauge of 0.0000000000000000000000016682390136105720344390625553663185390625 mm height are valid at a height of 0.00000000000000000000000083411950680528601722356252768315925390625 mm. The measurements of precipitation made with a rain gauge of 0.00000000000000000000000083411950680528601722356252768315925390625 mm height are valid at a height of 0.000000000000000000000000417059753402643008611781251384157965390625 mm. The measurements of precipitation made with a rain gauge of 0.000000000000000000000000417059753402643008611781251384157965390625 mm height are valid at a height of 0.000000000000000000000000208529876701321504305890625692078985390625 mm. The measurements of precipitation made with a rain gauge of 0.000000000000000000000000208529876701321504305890625692078985390625 mm height are valid at a height of 0.0000000000000000000000001042649383506607521529456253460394925390625 mm. The measurements of precipitation made with a rain gauge of 0.0000000000000000000000001042649383506607521529456253460394925390625 mm height are valid at a height of 0.00000000000000000000000005213246917533037707647281251730197465390625 mm. The measurements of precipitation made with a rain gauge of 0.00000000000000000000000005213246917533037707647281251730197465390625 mm height are valid at a height of 0.00000000000000000000000002606623458766518853823645625865097325390625 mm. The measurements of precipitation made with a rain gauge of 0.00000000000000000000000002606623458766518853823645625865097325390625 mm height are valid at a height of 0.0000000000000000000000000130331172938325944691182125432549665390625 mm. The measurements of precipitation made with a rain gauge of 0.0000000000000000000000000130331172938325944691182125432549665390625 mm height are valid at a height of 0.00000000000000000000000000651655864691629723455910625417228275390625 mm. The measurements of precipitation made with a rain gauge of 0.00000000000000000000000000651655864691629723455910625417228275390625 mm height are valid at a height of 0.00000000000000000000000000325827932345814886755453125208634135390625 mm. The measurements of precipitation made with a rain gauge of 0.00000000000000000000000000325827932345814886755453125208634135390625 mm height are valid at a height of 0.000000000000000000000000001629139661729074433772265625104317775390625 mm. The measurements of precipitation made with a rain gauge of 0.000000000000000000000000001629139661729074433772265625104317775390625 mm height are valid at a height of 0.0000000000000000000000000008145698308645372218861312552158888825390625 mm. The measurements of precipitation made with a rain gauge of 0.0000000000000000000000000008145698308645372218861312552158888825390625 mm height are valid at a height of 0.00000000000000000000000000040728491543226861094306562526089444415390625 mm. The measurements of precipitation made with a rain gauge of 0.0000000000000000000000000004072849154322686109430656252608944415390625 mm height are valid at a height of 0.00000000000000000000000000020364245771613430547153125130447222075390625 mm. The measurements of precipitation made with a rain gauge of 0.00000000000000000000000000020364245771613430547153125130447222075390625 mm height are valid at a height of 0.00000000000000000000000000010182122885806715273576562565221111035390625 mm. The measurements of precipitation made with a rain gauge of 0.00000000000000000000000000010182122885806715273576562565221111035390625 mm height are valid at a height of 0.00000000000000000000000000005091061442903357736883125326105555175390625 mm. The measurements of precipitation made with a rain gauge of 0.0000000000000000000000000000509106144290335773688312532610555175390625 mm height are valid at a height of 0.000000000000000000000000000025455307214516788684415625163052775825390625 mm. The measurements of precipitation made with a rain gauge of 0.000000000000000000000000000025455307214516788684415625163052775825390625 mm height are valid at a height of 0.00000000000000000000000000001272765360725839434223125815226388915390625 mm. The measurements of precipitation made with a rain gauge of 0.00000000000000000000000000001272765360725839434223125815226388915390625 mm height are valid at a height of 0.000000000000000000000000000006363826803629197171115625407631194475390625 mm. The measurements of precipitation made with a rain gauge of 0.000000000000000000000000000006363826803629197171115625407631194475390625 mm height are valid at a height of 0.000000000000000000000000000003181913401814598585557812520381557235390625 mm. The measurements of precipitation made with a rain gauge of 0.000000000000000000000000000003181913401814598585557812520381557235390625 mm height are valid at a height of 0.00000000000000000000000000000159095670090729929277891251

SAC, 8.

BIE S. Topical Water Management Problems in Farming Practice.

"Aktualne zagadnienia gospodarki wodnej w rolnictwie". Gospodarka Wodna. No. 3, 1953, pp. 85-91, 6 figs.

Review of the correlation between the maxima of sunspots and the course followed by the curves of mean temperatures — particularly in winter and spring. The author stresses the existence of an additional factor influencing the course of temperatures. He also deals with the stages of development of drought, and draws attention to the practicability of long-term meteorological forecasts. Importance to farming of the level of ground water, and of fluctuations of the ground water level according to the seasonal character of the programme of deep drainage in association with superficial irrigation. The author maintains that roughly 80 per cent of the total area of farm land calls for an improvement of water conditions. Complexity of the problem of water management. The large hydrological improvement scheme in Poland affecting the regulation and navigability of 3 000 km of rivers; flood protection of 700 000 hectares of arable land, thorough amelioration of roughly 220 000 hectares, and the utilisation of potential water-power resources amounting to the equivalent of 16 million kilowatt-hours per annum. This scheme includes the following land improvement works: the harnessing of mountain streams, the combating of soil erosion, the regulation of rivers, accurate drainage and irrigation of arable land; and the raising of the retention capacity of soils. Small reservoirs are more suitable for farming than large reservoirs located on a lower level.

10.3-304

Buc, Stanislaw and Marcilonek, Stanislaw, La condensation de la vapeur d'eau dans le sable et dans le gravier en vue des conditions climatiques en Pologne. [Condensation of water vapor in sand and in gravel in climatic conditions of Poland.] *Acta Geophysica Polonica*, Warsaw, 3(4):176-194, 1955. 7 figs., 6 tables, 7 refs. Polish summary p. 193-194. DWB, DLC—A very detailed report on the methods, procedures, and results of a study of the water balance in sands of different coarseness and gravel carried out with a series of lysimeters at the State Agronomic Research Station at Pulawy. Long period (1926-1939 and 1941-43) observations have shown that in conditions of the Polish climate, and especially in the summer period, a replenishment of the water reserves takes place in sandy soils by infiltration of rain and snow water. Subject Headings: 1. Water balance in sand 2. Lysimeters 3. Poland.—A.M.P.

551.579.5(438)

6

August 3, 1959

GW

1/

BBM
BAC, S.

ACTivities of the Group for Agriculture-Forestry and Improvements of the Committee on
Water Management.

p. 9 (Prace I Studia) No. 1, 1956, Warszawa, Poland

SO: MONTHLY INDEX OF EAST EUROPEAN ACCESSIONS (EEAI) LC, VOL. 7, NO. 1, JAN. 1958

45/20
BAC, S.

Method of investigating water consumption in the fields and in plant breeding and the application of the figures obtained in calculating hydrographic estimates for small basins.

p. 103 (Prace I Studia) No. 1, 1956, Warszawa, Poland

SO: MONTHLY INDEX OF EAST EUROPEAN ACCESSIONS (EEAI) LC, VOL. 7, NO. 1, JAN. 1958

BAC, S.

The problem of drainage in forestry. p. 1.

SYLWAN. (Wydział Nauk Rolniczych i Lesnych Polskiej Akademii Nauk i Polskie Towarzystwo Lesne) Warszawa, Poland (Journal on forestry issued by the Section of Agricultural and Forestry Sciences, Polish Academy of Sciences; and the Polish Society of Forestry; with English and Russian summaries. Includes supplements; Biuletyn Instytutu Badawczego Leśnictwa, bulletin of the Forest Research Institute; Biuletyn Instytutu Technologii Drewna, bulletin of the Institute of Wood Technology; Przegląd Dokumentacyjny Drzewnictwa, documentation of the Institute of Wood Technology; and Przegląd Dokumentacyjny Leśnictwa, documentation of the Forest Research Institute. Monthly)
Vol. 101, no. 7, July 1957

Monthly List of East European Accessions Index (EEAI), LC, Vol. 8, no. 6, June 1959
Uncl.

BAC, S.

Water needs of a meadow in the valley of the middle part of the Vistula River, p. 3.

Panstwowy Instytut Hydrologiczno-Meteorologiczny. WIADOMOSCI SLUZBY HYDROLOGICZNEJ I METEOROLOGICZNEJ.
Warszawa, Poland. Vol. 7, no. 1, 1959

Monthly List of East European Accessions (EEAI) LC, Vol. 8, no. 7, July 1959

Uncl.

BAG, Stanislaw

The peat problem in Poland. Postepy nauk roln 8 no.4:3-15 Jl-Ag '61.

BAC, Stanislaw

Need for adjustment of economic planning in the Beskidy Mountains to the climatic and soil conditions. Postepy nauk roln 9 no.2:45-55 Mr-Ap '62.

1. Wyższa Szkoła Rolnicza, Wrocław.

SCHMUCK, Adam; BAC, Stanislaw, prof. dr.; ZIPSER, Alina, mgr; LYKOWSKI, Bonifacy, mgr; GORCZAKOWNA, Maria

Droughts and high precipitation in the Wroclaw Voivodeship, 1950-1959. Czasop geograf 33 no.4:411-440 '62.

1. Katedra Meteorologii i Klimatologii, Wyzsza Szkoła Rolnicza, Wroclaw.

BAC, Stanislaw, prof. dr inz.

Water balance in Poland in the Year 2000. Gosp wodna 24
no.11:397-399 N '64.

BAC, V.

"Operational efficiency of forest railroads." p. 172.
(Narodni Sabor. Vol. 5, no. 4/5, Apr./May 1951, Sarajevo.)

SO: Monthly List of East European Acquisitions, Vol. 2, No. 9, Library of Congress, September
1953, Uncl.

BACA, F.

Premiere of Polish sportsmen in 1955.

p. 390
No. 17, Aug. 1955
KRIDLA VLASTI
Praha, Czechoslovakia

SO: Monthly List of East European Accessions. (EEAL). LC, Vol. 5, no. 2
February 1956, Uncl.

BACA, F.

The Slovak National Uprising.

p. 389
No. 17, Aug. 1955
KRIDL VLASTI
Praha, Czechoslovakia

SO: Monthly List of East European Accessions, (EEAL), LC, Vol. 5, no. 2
February 1956, Uncl.

BACA, Ferenc, inz.arch. (Backa Topola, Dure Salaja 1); SOBONJA, Petar,
tehn. (Backa Topola).

Industrial method of building at the Prvi Maj Building
Enterprise, Backa Topola. Tehnika Jug 18 no.10;Supplement:
Gradevinarstvo 17 no.10:1842-1844c 0'63.

Báca, 35

Distr: 4E2c(j) 7

Preparation of diallyl phthalate by azeotropic esterification. J. A. Weigner, V. Kudlacek, J. Báca, and St. Havel (Vysoká škola chem.-tech., Pardubice, Czech.). Chem. průmysl 8/33, 389-43 (1958). — The course of the prepn. of diallyl phthalate from phthalic anhydride and allyl alc. was studied by varying the amt. of catalyst, temp. of the azeotropic distn., type of catalyst, and molar ratio of reagents. The reaction rate increased with increasing amts. // of catalyst and with increasing temp. of the distn. Of the

solvents tested xylene was superior to PhMe or CH_2Cl_2 because of its higher b.p. H_2SO_4 was a better catalyst than toluenesulfonic acid or Katex FN, an ion-exchange resin. The mole ratio of the reactants had only a minor effect on the rate. Optimum conditions for the esterification were equimolar quantities of allyl alc. and phthalic anhydride, 0.5% H_2SO_4 as catalyst, and xylene as azeotropic agent yielding 81% product. The product, purified by treatment with 25% NaOH followed by vacuum distn., b. 147-50°.

Max Hellmann

7
2 may
1

BACA, JAN

Tvorba, Realizace a Rozdelovani Cisteho Duchodu v
Jednotnych Zemedelskych Druzstech. Praha, Statni
Nakladatelstvi Politicke Literatury, 1961.
297 p. Tables. 22cm.
Bibliographical Footnotes.

BAGA, K.

"Technicians and the Prospective Plan for Development of the Power Industry in
Czechoslovakia." p. 311. Praha, Vol. 4, no. 4, Apr. 1954.

SO: East European Accessions List, Vol. 3, No. 9, September 1954, Lib. of Congress

BACA, Oldrich, inz.

Development of logging mechanization in the Forest Enterprise Albrechtice and its economic evaluation. Les cas 11 no.3:273-302 Mr '65.

1. Forest Enterprise Albrechtice near Krnov. Submitted June 13, 1964.

BACA, W.

BACA, W. Reinforced-concrete bunker coatings hardened by the use of cast-iron shavings and filings. (Conclusion) p. 391. Vcl. 11, no. 12, Dec. 1956. Vol. 11, no. 12, Dec. 1956. MATERIAŁY BUDOWLANE. Warszawa, Poland.

SOURCE: East European Accessions List (EEAL) Vol. 6. No. 4--April 1957

BACHAK, MILOS

Chem

⁴ Esters of terephthalic acid Miroslav Bachak and František Káman Czech 85 736, Aug 4, 1980. A mixt. of *p*-Me₂C₆H₄CO₂Me (100), Me₂C₆H₄CO₂H 200, and Co naphthenate 0.5 part was oxidized at 170° by conveying by means of a turbo-stirrer (1) under the surface of the melt at a rate 0.33 l. O/min. After cooling, the crystals of *p*-Me₂C₆H₄CO₂H were filtered off and the mother liquor used in the next batch. Yields were 85%. L. J. Urbánek

BACAK, M

PHASE I BOOK EXPLOITATION

SLOVAK/4311

Lacko, Vladimír, Engineer, Milos Bačák, Engineer, František Hadobáš, Engineer,
František Kamas, Antonín Majrich, Doctor, Engineer, and Bohumil Piller

Polyesterové vlákna (Polyester Fibers) Bratislava, Slovenské vyd-vo tech. lit-ry,
1959. 291 p. 1,200 copies printed.

Reviewers: Artur Stoy, Docent, Engineer, and Štefan Tomašovič, Engineer; Tech. Ed.:
Klára Kováčová, Engineer; Chief Ed.: Pavol Holéczy, Engineer;

Resp. Ed.: Klára Kováčová, Engineer.

PURPOSE: This book is intended for senior staff members in the chemical and textile industries, and for students in special schools. It may also be of interest to the general reader.

COVERAGE: The book describes the treatment of raw materials for production of polyester fibers, the technology of semiproducts, and the production, finishing, dyeing and spinning of polyester fibers. Important theoretical concepts concerning the properties of polyesters and polyester fibers are discussed. This is the first book in Slovak on polyester fibers describing the theoretical principles and steps in the production of synthetic fibers placing particular emphasis on the production of polyester fibers.

Card 1/42-

Polyester Fibers

SLOVAK/4311

sis on features of the production of polyethyleneterephthalic fibers. Material is included on variations in the production process and on recent developments in the field. The following personalities are mentioned: Docent Engineer Stoy, Engineer Tomášovič, Doctor Engineer Černák, Engineers Marek and Hrivnák of the Vyskumný ústav umělých vláken (Research Institute of Synthetic Fibers) in Svit, Doctor Engineer Hrušovský of the Silon plant at Plana on the Lužnica River. Diagrams were drawn by Šalingová; Pálušová and Michalidesová provided photographs and X-rays. There are bibliographies at the end of every chapter.

TABLE OF CONTENTS:

Preface	11
Abbreviations	13
Introduction	15
I. Development and Significance of Polyester Fibers	17
1. Discovery and development of polyester fibers	17
2. Economic and industrial importance of polyester fibers	22

Card 2/12

COUNTRY	: Czechoslovakia	R-32
CATEGORY	:	
ABS. JOUR.	: RZhKhim., No. 22 1959 No.	80505
AUTHOR	: Bacak, M.	
INST.	: Not given	
TITLE	The Regeneration of Polyethyleneterephthalate	
OPIN. PIZ.	Chem Prumysl, 9, No 2, 108-109 (1959)	
ABSTRACT	A critical analysis of existing processes for the regeneration of polyethyleneterephthalate [Dacron, Terylene] has led the author to conclude that the most efficient process is alcoholysis with methanol, leading to the formation of the dimethyl ester of terephthalic acid. The latter is subjected to a purification and reused in the polymerization. S. Vol'fson	
CARD	1/1	

BACAL, Kazimierz, mgr inz., st. asystent

Profilographometric study of the shape of the profiles of skulls.
Mechanika Wroclaw no.9:111-120 '63.

1. Department of Metal Machining of the Technical University,
Wroclaw.

BACAL, Kazimierz, dr inz.

Studies on the conditions for bear formation during gray cast-
iron turning. Przegl mech 22 no. 13:616 10 Jl '63.

1. Katedra Obrobki Metalu, Politechnika, Wroclaw.

BACAL, M.; DOBRETOV, L. N. [Dobretsov, L.N.]

Physical principles of the method of Millikan vacuum condenser, Studii
cerc fiz 12 no.2:325-334 '61.

1. Institutul politehnic Leningrad.

(Cosmic rays) (Vacuum apparatus)
(Condensers(Electricity))

AFINOGHENOV, L. P. [Afinogenov, L. P.]; BACAL, M.

Stabilization of a microscopic particle, charged in a Millikan vacuum condenser. Studii cerc fiz 12 no.2:449-460 '61.

l. Institutul fizico-tehnic "A.F.Ioffe" al Academiei de Stiinte a U.R.S.S.

(Vacuum apparatus) (Condensers(Electricity))
(Cosmic rays)

BACAL, M.

Direct transformation of the heat in electric energy. Studii
cerc fiz 14 no.5:589-618 '63.

1. Institutul de fizica atomica, Bucuresti.

BACALBASA, N., conf.

Fishing terminology. Ind alim anim 11 no.3:91-93 Mr'63

1. Institutul politehnic, Galati.

VJ 12 5 20 1 C 11 - 10 1

Country	: RUMANIA	H-26
Category	: Chemical Technology. Carbohydrates and Their Processing	
Abs. Jour	: Ref. Zhur-Khimiiye, No 14, 1959, No 51326	
Author	: Bacalbasa, N.	
Institute	: -	
Title	: Utilization of Seaweeds in the Rumanian Peoples Republic	
Orig Pub.	: Rev. ind. aliment. prod. animale, 1958, No 5, 1-3	
Abstract	: Review of works, conducted by the Soviet and Rumanian scientists pertaining to the under-water flora of the Black Sea. Described are refining methods applied to seaweeds that consist in the boiling of seaweeds in a 1% KOH solution for 8-12 hours, followed by the separation of agaroids and their purification by filtration, conducted with the addition of activated charcoal. The thickened mass is then subjected to evaporation, drying in drum type driers, granulation and packing.--D.Bronshteyn	
Card:	1/1	

54CP20660D

CIORANU, Dr.
SUCHIUS, Given Name

Country: Rumania

Academic Degrees: [not given]

Affiliations: [not given]

Source: Timisoara, Timisogara Medicala, No 2, Jul-Dec 60, pp 45-49.

Data: "On the Importance of the Variants of the Extra-Hepatic
Biliary Routes for the Treatment and Surgery of the
Biliary Routes."

Co-authors:

BACALOIU, D. [Degree and affiliation not given]

54CP20660D

BUSILA, V.T.; ALEXANDRESCU, R.; BACALOGIU, D.; in colaborare cu D. Sarateanu
si Elena Oprescu-Lisievici..

Clinical and pathomorphological aspects of an epidemic produced
by the ornithosis virus. Stud. cercet. inframicrobiol., Bucur. 11
no. 2:187-193 '60.
(ORNITHOSIS epidemiol.)

BUSILA, V. T., prof.; VASILESCU, I., dr.; CUCUTUZ, L., dr.; ALEXANDRESCU, R., dr.;
POPIAN, R., dr.; FITARAU, A., dr.; PLACINTA, A., dr.; STAMBOLIU, D. M., dr.;
BACALOGLU, D., dr.; PANA, G., dr.; NOVACOVICI, O., dr.; COTLEAREVSCHI, V.,
dr.; COTLEAREVSCHI, E., dr.

Clinical and biological characteristics of a focus of trichinosis.
Med. intern., Bucur 13 no.2:227-236 F '61.

1. Clinica de boli contagioase, Timisoara (for Bacaloglu). 2. Spitalul
si Sanepidul Orsova (for Cotlearevschi).

(TRICHINOSIS)

REICHEL, J.; BACALOGLU, R.; SCHMIDT, W.

IR-spectra of p-substituted N-phenylbenzamides. Rev chimie
Roum 9 no. 4:299-318 Ap '64.

1. Laboratory of Organic Chemistry, Scientific Research
Center of the Rumanian Academy, Timisoara.

OSTROGOVICH, G.; BACALOGLU, R.

On the determination of biuret in the mixtures with urea, cyanuric acid, ammonium chloride, and other products that might result from the thermolysis of urea. Studii chim Timisoara 7 no.3/4:277-283
Jl-D '60. (EEAI 10:9/10)

1. Institutul politehnic Timisoara. Facultatea de chimie industriala
Laboratorul de chimie organica.

(Biuret) (Mixtures) (Urea) (Cyanuric acid)
(Ammonium chloride)

OSTROGOVICH, G.; BACALOGLU, R.; NEMES, A.; MORARU, M.

A kinetic study of the thermolysis of rea and subsequent transformations. I. Mechanism of the formation of biuret, triuret, and cyanuric acid at the thermolysis of urea itself and in the presence of some acid agents. Studii chim Timisoara 8 no.1/2:59-78 Ja-Je '61.

(EEAI 10:9)

1. Institutul Politehnic Timisoara; Laboratorul de Chimie Organica.

(UREA) (BIURET) CYANURIC ACID)
(HEAT OF DISSOCIATION)

OSTROGOVICH, G.; BACALOGLU, R.

Combined and simple molecular association in the mixtures of melamine, ammeline, and cyanuric acid. Studii chim Timisoara 9 no.3/4:273-289 Jl-D '62.

1. Institutul Politehnic din Timisoara, Laboratorul de Chimie organica.

OSTROGOVICH, G.; BACALOGLU, R.; NEMES, A.; CATALINA, Elena; NUTIU, Maria

Infrared spectra in the field of amidic derivatives of carbonic acid.
Pt.1. Studii chim Timisoara 10 no.1:71-100 Ja-Je '63.

1. Timisoara, Institutul Politehnic, Laboratorul de Chimie Organica.

OSTROGOVICH, G.; BACALOGLU, R.; CATALINA, Elena

Infrared spectra of the amidic derivatives of carbonic acid.
Pt. 2. Studii chim Timisoara 10 no.2:143-166 Jl-D'63.

1. Institutul Politehnic din Timisoara, Laboratorul de chimie
organica.

OSTROGOVICH, G.; BACALOGLU, R.; NEMES, A.

Infrared spectra of the amidic derivatives of carbonic acid.
Pt.3. Studii chim Timisoara 10 no.2:167-177 Jl-D'63.

REICHEL, J.; BACALOGLU, R.; Schmidt, W.

Infrared spectra of some p-substituted N-phenylbenzamide.
Studii cerc chim 12 no. 4:299-317 Ap '64.

1. Center of Scientific Research of the Rumanian Academy,
Timisoara,

BACALOVA, L.; TODOROV, J.; DAMYANOVA, M.

Studies of some serum enzyme activities in rachitic children.
Nauch. tr. Vissash med. inst. Sofiia 43 no.1:25-28 '64.

1. Chair of Pediatrics, (Director: Prof. L. Racev) and Chair of
Clinical Laboratory at the Postgraduate Medical Institute,
(Director: Prof. J. Todorov).

BACAN, M

Bacan, M. Cartes icchistului. Ed 2. revazuta si adaugita. (Bucuresti)
Editura Confederatiei Generale a Minclii, 1951 p.166 (colectia tehnica,
5) (The fireman's handbook)

SG: East European, LC, Vol. 2, No. 12, Dec. 1953

BACANARU, I.

Studies on human settlements between the Milcovat, Cilniste, and Arges Rivers, p. 109.

PROBLEM DE GEOGRAFIE. (Academia Republicii Populare Romine. Institut de Cercetare Geografice) Bucuresti, Rumania. Vol. 6, 1959.

Monthly list of East European Accessions (EEAI) LC, Vol. 9, no. 2, August, 1959.

Uncl.

FACAKANU, I.

Studies on human settlements between the Milcovat, Cliniste, and Arges Rivers. p. 109

PROBLEME DE GEOGRAFIE. (Academia Republicii Populare Române. Institutul de Cercetări Geografice) Bucuresti, Romania. Vol. 6, 1959.

Monthly list of East European Accessions (EEAI) LC, Vol. 9, No. 2, Feb. 1960.

Uncl.

BACANARU, Ion

Territorial distribution of industries in the Arges region. Probleme
geog 8:367-384 '61.

COTET, P., conf. univ.; BACANARU, I., cercetator (Bucuresti)

The Banat region; geographic characterization. Natura Geografie
17 no.2:18-35 Mr-Ap '65.

HERBST, C.; BACANARU, I.; CALOIANU, N. (Bucuresti)

Contributions to the study of territorial concentration
types of the industry in Romania, Natura Geografie 16
no.3:9-16 My-Je '64.

POPESCU, Valerian, prof.; BACANU, C.G.

The action of silver proteinate (protargol) in actinomycosis. Rumanian
M Rev. no.3:84-87 Jl-S '60.
(ACTINOMYCOSIS therapy) (SILVER PROTEINS therapy)

ZOSIN, C., conf.; BARBU, N.; BACANU, Gh.; IANOVICI, Eugenia

Investigation of renal function with the aid of plasma purification methods; measurement of glomerular infiltrates with sodium hyposulfite. Rev.st.med., med. int., Bucur. 6 no.4:59-68 Oct-Dec 54.

1. Clinica a II-a medicala, I.M.F. Timisoara Comunicat in sedinta sin 3 iunie 1953 a Societatii stiintelor medicale sectia boli interne, filiala Timisoara

(KIDNEY FUNCTION TESTS

glomerular filtration, measurement with sodium hyposulfite)

(SODIUM

hyposulfite, in kidney funct. test)

ZOSIN, C., Prof.; ELIAS, St.; BACANU, Gh.; BARBU, N.; IANOVICI, E.

Measurement of the coefficient of clearance of iodated compounds
for determination of the effective renal blood flow. Med. int.,
Bucur. 7 no.4:127-136 Oct-Dec 55.

1. Clinica a II-2 med. IMF Timisoana.

(KIDNEYS, blood supply

determ. of effective renal flow by clearance of
neorenal)

(CONTRAST MEDIA

neorenal clearance in determ. of effective renal
blood flow)

DIGITALIZA

ZOSIN, C., Prof.; POPESCU, A., dr.; BACANU, Gh., dr.; BARBU, N., dr.

Magnesium sulfate in determination of arterial circulation rate.
Med.int., Bucur. 8 no.5:711-715 Sept 56.

1. Clinica a 11-a medicala, Timisoara.

(BLOOD CIRCULATION

rate of flow, peripheral, determ. with magnesium sulfate
& fluorescein)

(VASCULAR DISEASES, PERIPHERAL, diagnosis

determ. of rate of arterial blood flow in extremities,
method using magnesium sulfate)

(MAGNESIUM SULFATE

method of determ. of arterial circ. rate)

EXCERPTA MEDICA Sec 16 Vol 7/5 Cancer May 59

1662. Primary tumour of the pericardium with multiple metastases
Tumoare primativa de pericard cu metastaze multiple. BĂGANU Gh., BARBU N.,
DIACONESCU I., JICMAN L., SABO I. and SCHNEIDER I. Clin. a III-a Med., Timișoara
Med. interna (București) 1958, 10/6 (919-923)

The clinical, radiological, ECG and morbid-anatomical findings in a case of reticulo-
endothelio-angiosarcoma of the pericardium with myocardial metastases are exposed.
Stress is laid on the youth of the patient, the dimensions reached by the tumour and
the rarity of these cases.

Nicolaescu - Bucharest

BACANU, Gh.

RUMANIA

BACANU, Gh., MD; GAVRILESCU, St., MD.

Medical Clinic No I Timisoara, Nutrition Section (Clinica I
Medicala Timisoara, Sectia Nutritie) - (for all)

Bucharest, Viața Medicală, No 4, 15 Feb 63, pp 247-256.

"Actualities in the Field of Nutrition Diseases."

(2)

BACANU, Gh., MD; TURCANU, Valentina, MD.

ROMANTÀ

Section of Nutrition and Dietetics, Medical Clinic I
(Sectia nutritie-dietetica, Clinica I medicala);
Director: Professor H. Aubert. - (for all)

Bucharest, Vîata Medicală, No 9, 1 May 63, pp 621-625

"Primary Cancer of the Pancreas and Diabetes Mellitus"
(Paper submitted to the U.S.S.M., Benét Branch, at the
meeting of 30 May 1962.)

BACANU, Gh., dr.; SAVIN, Maria, chim.; MUSTERIU, Hortensia, chim.;
MEMET, Alise, extern.

Criteria of hypoglycemic sulfonylurea treatment in diabetes
mellitus. Med. intern. 15 no.8:957-962 Ag '63.

1. Lucrare efectuata la Spitalul de adulti nr. 1, Timisoara
(Sectia nutritie-dietetica si Centrul antidiabetic).
(DIABETES MELLITUS) (ANTIDIABETICS)

RUMANIA

BACANU, Gh., MD; GAVRILESCU, S., MD; AIGHESCU, Lucia, MD.

Dietetic Nutrition Section, Clinical Hospital no 1 for
Adults, Timisoara (Sectia nutritie-dietetica, Spitalul
clinic de adulti nr. 1, Timisoara) - (for all)

Bucharest, Viiata Medicala, No 2, 15 Jan 64, pp 107-114

"Recent Contributions to the Therapy of some Nutritional
Diseases."

GAVRILESCU,S., dr.; BACANU, Gh., dr.; COREANU, Gabriela, dr.; ANGHELESCU, Lucia, dr.

Considerations on some bone changes in diabetic gangrene. Med. intern. (Bucur.) 16 no.11:1351-1357 N '64

1. Lucrare efectuata in Clinica I medicala, I.M., Timisoara.

BACANU, Gh., dr.; ANGHELESCU, Lucia, dr.; POPA, Lidia, dr.

Detection of diabetes mellitus in patients with myocardial infarct. Med. intern. (Bucur.) 17 no.4:413-416 Ap '65.

1. Lucrare efectuata in Sectia de nutritie-diabet a Clinicii I medicala, I. M. Timisoara (director: conf. St. Gavrilescu).

BACANU, Ion, prof.

Excursion to Peștera Dimbovicioara. Natura Geografie 12
no. 6:132-134 N-D '60.

1. Scoala Medie nr.3 Pitesti; Secretar al Fil. Pitesti a
Societatii de Stiinte Naturale si Geografie din R.P.R.

BACANU, I., prof. (Pitesti)

Itineraries for the excursions in the Arges region.
Natura Geografie 14 no.2:52-58 Mr-Ap '62.